Appl. No. 10/517,321

Amendment dated: July 6, 2006

Reply to OA of: February 6, 2006

Amendments to the specification:

Please replace the paragraph beginning at page 13, line 27 with the following rewritten

paragraph:

--As shown in Fig. 8, the connecting station 100 is comprised of a connecting rack or

panel 112 having a plurality of connecting receptors or sockets 118 for docking a

corresponding number of cells 10. Each socket 118 may be shaped as a depression

in the panel front and may have a dent 120119 to mate with an indent 18 of the cell 10

to prevent improper orientation on insertion of cell 10 in socket 118.

Please replace the paragraph beginning at page 14, line 27 with the following rewritten

paragraph:

--Returning to Fig. 1a, the flowing unit 70 is composed of a fluid distributing system

including fine caliber tubing and valves having small dead volumes to handle the usually

small volumes of test solution 83 that are obtained, for example by condensation of an

evaporated volume of air that may contain the analyte to be detected by the system of

the invention. Example of tubing is standard HPLC PEEK (polyetheretherketone) or

stainless steel tubing having an inner diameter of 0.25 mm to achieve acceptable

sample dispersion and yet not too large pressure loss in the system.

- 2 -

Appl. No. 10/517,321

Amendment dated: July 6, 2006 Reply to OA of: February 6, 2006

This listing of claims will replace all prior versions and listings of claims in the application.

Listing of Claims:

Claims 1-9(canceled).

10(currently amended). A multiple piezoelectric crystal microbalance device comprising a connecting station (100,101) for receiving and individually operating an array of piezoelectric crystal microbalances comprising:

a connecting panel (112; 113) having an array of cell connecting receptors (118), each <u>cell connecting</u> receptor comprising a receptor connector portion (120) for <u>automatic</u> mating operative engagement with a cell connector portion (24) of <u>each a</u> piezoelectric crystal microbalance flow-through cell (10), <u>upon plugging said flow-through cell (10) into the connecting station (100,101), wherein</u>

each the receptor connector portion (120) comprises

a pair of electric connecting ports (126, 128) for communication with a power and measurement means (130) for oscillating a piezoelectric crystal (50) carrying two electrodes (56,62) in a cell compartment (34) of one operatively engaged flow-through cell (10) and for measuring oscillating characteristics of the piezoelectric crystal (50); and comprises

a pair of fluid connecting ports (122, 124) for communication with flowing means (70) for <u>uninterrupted</u> flowing <u>of</u> a solution (75) and a test solution aliquot (83) to, and through, the cell compartment (34).

11(original). The multiple piezoelectric crystal microbalance device according to claim 10, wherein the individually operated piezoelectric crystal microbalances are electrostatically and electromagnetically shielded from each other.

Appl. No. 10/517,321

Amendment dated: July 6, 2006

Reply to OA of: February 6, 2006

12(currently amended). The multiple piezoelectric crystal microbalance device

according to claim 11, wherein the connecting station (100) comprises connection

means (112) for[[,]] serial interconnection of the flowing of the solution (75) and test

solution aliquot (83) to and through the cell compartment (34) of the individual flow-

through cells (10).

13(currently amended). The multiple piezoelectric crystal microbalance device

according to claim 11, wherein the connecting station (101) comprises connection

means (113) for[[,]] parallel connection of the flowing of the solution (75) and test

solution aliquot (83) to and through the cell compartment (34) of the individual flow-

through cells (10).

14(original). The multiple piezoelectric crystal microbalance device according

to claim 11, further comprising grounding means (108) for electrical grounding of the

flow solution (75) and the test solution aliquot (83) to the cell compartment (34) of each

of the flow-through cells (10).

Claims 15-34(canceled).

- 4 -